



2-Port Desktop KVM Switch with 2 KVM Cable Kits (PS2)

MODEL NUMBER: B022-002-KT-R



Description

Tripp Lite's B022-002-KT-R 2-port KVM Switch is the optimal solution for controlling 2 computers from one keyboard, mouse and monitor. Installation is a snap - just connect the PCs using the included PS/2 cable kits. P776-Series USB KVM cable kits are available separately for connection of USB computers. Easily switch between computers via front-panel push buttons or keyboard hotkey commands.

Features

- Control 2 computers from a single keyboard, mouse, and monitor
- Comes with 2 PS/2 KVM cable kits
- P776-Series USB KVM cable kits are available separately for connection of USB computers
- Supports VGA, SVGA, or Multisync monitors
- · Easy to install no software required
- Easily select a computer via front-panel push buttons or keyboard hotkeys
- Auto Scan function to monitor computer operation
- Supports Microsoft IntelliMouse and the scrolling wheel on most mice
- Superior video quality up to 2048x1536; DDC2B
- External power not required
- Compatible with all major operating systems except Mac and Sun

Specifications

OVERVIEW	
UPC Code	037332120236

Highlights

- Control 2 computers with 1 keyboard, monitor and mouse
- Comes with 2 PS/2 KVM cable
- P776-Series USB KVM cable kits are available separately for connection of USB computers
- Simple plug-and-play design
- Ultra-slim design takes up minimal space
- Compatible with all major operating systems except Mac and Sun

System Requirements

- VGA, SVGA or Multisync
 Monitor with an HD15 port
- PS/2 mouse
- PS/2 keyboard
- PS/2 or USB computer
- Compatible with all major operating systems except Mac and Sun

Package Includes

- B022-002-KT-R 2-port KVM Switch
- (x2) PS/2 KVM Cable Kits
- PS/2 console cable kit
- Owner's Manual





Users	1	
Console	No	
Max CPU	2	
Technology	PS/2; USB (all versions); VGA/SVGA	
PHYSICAL		
Shipping Dimensions (hwd / in.)	6.80 x 2.50 x 9.40	
Shipping Dimensions (hwd / cm)	17.27 x 6.35 x 23.88	
Shipping Weight (lbs.)	2.00	
Shipping Weight (kg)	0.91	
Unit Dimensions (hwd / in.)	1 x 5 x 3.25	
Unit Dimensions (hwd / cm)	2.54 x 12.7 x 8.26	
Unit Weight (lbs.)	0.73	
Unit Weight (kg)	0.33	
Color	Silver	
LCD Monitor (in.)	Not Applicable	
LCD Monitor (cm)	Not Applicable	
COMMUNICATIONS		
Port Control	Push Buttons, Hotkeys	
IP Remote Access	No	
CONNECTIONS		
Ports	2	
PC/Server Connections	PS/2; USB; VGA	
Included KVM Cable (Equipment Side) - Connector 1	HD15 (Male)	
Included KVM Cable (Equipment Side) - Connector 2	(x2) MiniDIN6 (Male)	
WARRANTY		
Product Warranty Period (Worldwide)	3-year limited warranty	

© 2018 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: https://www.tripplite.com/products/product-certification-agencies